

THERMAL INSTABILITY OF COMPRESSIBLE FLUID LAYER IN A POROUS MEDIUM : EFFECT OF WEAK MAGNETIC FIELD AND LOW THERMAL CONDUCTIVITY

SUBODH KUMAR RANA

Department of Mathematics, M.M. (PG) College Modinagar- 201204, INDIA

E-mail : skrmmpg@gmail.com

Received : June 5, 2013

Abstract : The paper examines, within the framework of linear analysis, the thermal instability of compressible fluid layer in a porous medium in the presence of weak magnetic field and low thermal conductivity. The important results are obtained in this paper depend on $DT_0 + g/C_p$.

Keywords : Thermal instability, compressible fluid layer, porous medium, weak magnetic field, low thermal conductivity.

2010 Mathematics Subject Classification : 76S05

1. Introduction

Instability of flows in a porous medium has been extensively studied by enormous research workers on the basis of Darcy's law[6] which completely neglects the viscous forces. An excellent review has been given by Scheidegger[13] and Yih[15]. Brinkman[4] proposed a plausible modification to Darcy's law that takes into account the viscous forces. Jaimala and Agrawal [9], unlike Irmay [8] and Beck[3], investigated a more physically realistic model in which the inertia and viscous forces are included in their usual forms to account for the flows with high flow rates, high permeability and high viscous forces.

Instability of compressible and incompressible flows has been studied extensively by a number of research workers in past few decades. In almost all such investigations, the Boussinesq's approximation is used to simplify the equations of motion. Jeffreys [11] tried to provide a justification of under certain conditions. If

the vertical dimension of the fluid be much less than the scale height and the fluctuations in temperature, pressure and density, introduced due to the Boussinesq's approximation for steady, infinitesimal motions of compressible fluids and Spiegel and Veronis [14] simplified the set of equations governing the compressible flows motion, do not exceed their total static variations, then the flow equations are same as for incompressible fluids, the static temperature gradient being replaced by its excess over the adiabatic gradient and the specific heat at constant volume C_v by that at constant pressure C_p .

Using the model as suggested by Spiegel and Veronis [14], Banerjee and Agrawal [1] investigated the thermal instability of parallel shear flows in the presence of both adverse and non-adverse temperature gradients. In an important paper, Bansal and Agrawal [2] investigated the thermal instability of a compressible shear flow with weak applied magnetic field in the presence of adverse or non-adverse temperature gradient.

In the present analysis, we have examined within the frame work of linear analysis, the thermal instability of a compressible shear layer in a porous medium. Though, some literature has been reported in which magnetic field destabilizes a wave number range known to be stable in its absence [Kent [12], Gilman [7], Jain [10]], in most of the situations magnetic field has a stabilizing effect.

As explained by Chand and Agrawal [5], the problem under investigation provides a reasonably good mathematical model to a narrow layer of atmosphere above earth's surface so that the curvature effects can be neglected and the boundaries be taken as horizontal, the lower boundary (the earth's surface) being rigid and the upper boundary being free. Temperature variations are due to the Sun and the pattern of temperature variations (increasing or decreasing in the vertical direction) depends upon the place/ time of investigation. The assumption of small thermal conductivity not only simplifies the mathematical analysis, thus leading to a number of interesting results, but also is important in the context of physical

situations in which the transfer of heat is not instantaneous (case of very large thermal conductivity), rather it is slow. We consider the physical situation is which the wind speed is small so that our study is restricted to the case of low Mach number. The study is also restricted to the case of large wave numbers only.

2. Formulation of the problem

Consider an unidirectional flow of a compressible, viscous and heat conducting fluid in the presence of a horizontal magnetic field in a homogeneous and isotropic porous medium, confined between two infinite parallel plates situated at a distance d apart. In a cartesian frame of reference, the axis of x is in the main flow direction and the axis of z is against gravity. Boundaries are maintained at constant temperatures T_1 and T_2 respectively. The layer depth is small enough so that it is much less than the scale height as defined by Spiegel and Veronis. The basic state under investigation is, therefore, characterized by

$$\left. \begin{aligned} \mathbf{V} &= [0, 0, 0], & T &= T(z), & \mathbf{H} &= (H, 0, 0) \\ \rho &= \rho(z), & \text{and} & & p &= p(z), \end{aligned} \right\} \dots(1)$$

Where V , T , H , ρ and P are the fluid velocity, temperature, magnetic field, density and pressure respectively.

Further, $T(z) = D(T_0)z + T_1$,

$$p(z) = p_m - g \int_0^z (\rho_m + \rho_0) dz$$

and $\rho(z) = \rho_m [1 - \alpha_m (T - T_m) + k_m (p - p_m)]$

The time independent solution of the governing equations does not change in the presence of a uniform magnetic field and therefore the basic velocity distribution remains the same as in Chand and Agrawal. DT_0 is the uniform static temperature gradient and α_m and k_m are give as

$$\alpha_m = \frac{1}{T_m} = - \left(\frac{1}{\rho} \frac{\partial \rho}{\partial T} \right)_m = \alpha \text{ (say)} \quad \text{and} \quad k_m = \left(\frac{1}{\rho} \frac{\partial \rho}{\partial p} \right)_m \dots(2)$$

3. Perturbed state solution and the linearized perturbation equations

We now suppose that the solution in the basic state is slightly perturbed so that every physical quantity is assumed to be the sum of a mean and a fluctuating component, later designated as primed quantity and assumed to be very small in comparison to its basic state value. The small disturbances are assumed to be the functions of the space as well as time variables

Following Spiegel and Veronis, the linearized perturbation equations of motion, continuity, heat conduction and magnetic field are

$$\frac{\rho_m}{\phi} \frac{\partial u'}{\partial t} = -\frac{\partial p'}{\partial x} + \mu \left(\frac{1}{\phi} \nabla^2 - \frac{1}{k_1} \right) u', \quad \dots (3)$$

$$\frac{\rho_m}{\phi} \frac{\partial v'}{\partial t} = -\frac{\partial p'}{\partial y} + \mu \left(\frac{1}{\phi} \nabla^2 - \frac{1}{k_1} \right) v' + \frac{H}{4\pi} \left(\frac{\partial h'_y}{\partial x} - \frac{\partial h'_x}{\partial y} \right), \quad \dots (4)$$

$$\frac{\rho_m}{\phi} \frac{\partial w'}{\partial t} = -\frac{\partial p'}{\partial z} + \mu \left(\frac{1}{\phi} \nabla^2 - \frac{1}{k_1} \right) w' + \frac{H}{4\pi} \left(\frac{\partial h'_z}{\partial x} - \frac{\partial h'_x}{\partial z} \right) + g\alpha\rho_m\theta', \quad \dots (5)$$

$$\frac{\partial u'}{\partial x} + \frac{\partial v'}{\partial y} + \frac{\partial w'}{\partial z} = 0, \quad \dots (6)$$

$$\frac{\partial h'_x}{\partial t} = -\frac{H}{\phi} \left[\frac{\partial v'}{\partial y} + \frac{\partial w'}{\partial z} \right], \quad \dots (7)$$

$$\frac{\partial h'_y}{\partial t} = \frac{H}{\phi} \frac{\partial v'}{\partial x}, \quad \dots (8)$$

$$\frac{\partial h'_z}{\partial t} = \frac{H}{\phi} \frac{\partial w'}{\partial x}, \quad \dots (9)$$

$$\frac{\partial h'_x}{\partial x} + \frac{\partial h'_y}{\partial y} + \frac{\partial h'_z}{\partial z} = 0, \quad \dots (10)$$

$$\text{and } \frac{\partial \theta'}{\partial t} + \frac{w'}{\phi} (DT_0 + g/C_p) = \kappa \nabla^2 \theta', \quad \dots(11)$$

where a dash denotes the perturbation quantity and $\kappa = \kappa' / \rho_m C_p$, ϕ , k_1 and μ are respectively the thermal conductivity, medium porosity, medium permeability and the coefficient of viscosity. $DT_0 - (-g/C_p)$ is the excess over the adiabatic gradient $(-g/C_p)$ and the other symbols have their same meaning as in Spiegel and Veronis.

We analyse the perturbations into normal modes, taking dependence of any perturbation quantity $f'(x, y, z, t)$ of the form.

$$f'(x, y, z, t) = f(z) \exp \left[i \left(k_x x + k_y y - \frac{k_x C}{\phi} t \right) \right],$$

where k_x and k_y are the real wave numbers in x and y directions, $k = \sqrt{k_x^2 + k_y^2}$ and C , in general, is complex.

Now eliminating various physical quantities from the resulting equations and non-dimensionalising the resulting equations, using $(k^*, k_x^*, D^*) = d(k, k_x, D)$ and $(w^*, C^*) = \frac{1}{U_0}(w, C)$, where d is the characteristic length and U_0 is the characteristic velocity, we obtain after omitting the asterisks, the following non-dimensional equations

$$\begin{aligned} k^2 (-C - ik_x^{-1} R_D^{-1}) w &= D \{ (-C - ik_x^{-1} R_D^{-1}) Dw \} \\ -S(D^2 - k^2) \left\{ -\frac{w}{C} \right\} + ik_x^{-1} R_e^{-1} (D^2 - k^2)^2 w - \frac{iJ_0 k^2 \theta}{k_x} &\dots(12) \end{aligned}$$

$$\text{and } \kappa (D^2 - k^2) \theta + \frac{ik_x d U_0}{\phi} C \theta = \frac{U_0 d^2 (DT_0 + g/C_p)}{\phi} w, \quad \dots(13)$$

where

$$R_D^{-1} = \frac{\mu\phi^2 d}{k_1 \rho_m U_0}, \quad R_e^{-1} = \frac{\mu\phi}{\rho_m d U_0},$$

$$S = \frac{H^2 \phi^2}{4\pi U_0^2 \rho_m} \quad \text{and} \quad J_0 = \frac{g\alpha\phi^2 d}{U_0^2}.$$

The necessary boundary conditions are

$$w=0 \text{ at } z=0 \text{ and } d, Dw=0 \text{ at } z=0, D^2w=0 \text{ at } z=d \text{ and } \theta=0 \text{ at } z=0 \text{ and } d. \dots(14)$$

Now multiplying the equation (12) by w^* (complex conjugate of w) on both sides and taking the conjugate of (13), multiplying by θ , and then integrating over the range of z , we get

$$k^{-1}R_e^{-1}I_1 + (k^{-1}R_D^{-1} - n)I_2 = \frac{S}{n}I_2 + J_0k \int \theta w^* dz. \dots(15)$$

$$\text{and } -I_3 + \frac{kdU_0n^*}{\phi\kappa}I_4 = \frac{U_0d^2(DT_0 + g/C_p)}{\phi\kappa} \int \theta w^* dz, \dots(16)$$

where $I_1 = \int (|D^2w|^2 + 2k^2|Dw|^2 + k^4|w|^2) dz$

$$I_2 = \int (|Dw|^2 + k^2|w|^2) dz.$$

$$I_3 = \int (|D\theta|^2 + k^2|\theta|^2) dz$$

and $I_4 = \int |\theta|^2 dz.$

Now to eliminate $\int \theta w^*$ from equations (15) and (16), we get

$$-J_0kI_3 + \frac{k^2dU_0J_0n^*}{\phi\kappa}I_4 = \frac{U_0d^2(DT_0 + g/C_p)}{\phi\kappa} \left[k^{-1}R_e^{-1}I_1 + (k^{-1}R_D^{-1} - n)I_2 - \frac{Sn^*}{|n|^2}I_2 \right]. \dots(17)$$

Again substituting $n = n_r + in_i$ in the equation (17) and then equating real and imaginary parts, we get

$$\begin{aligned}
 -J_0 k I_3 + \frac{k^2 dU_0 J_0 n_r}{\phi \kappa} I_4 &= \frac{U_0 d^2(DT_0 + g/C_p)}{\phi \kappa} \left[k^{-1} R_e^{-1} I_1 \right. \\
 &\left. + (k^{-1} R_D^{-1} - n_r) I_2 - \frac{S n_r}{|n|^2} I_2 \right] \quad \dots(18)
 \end{aligned}$$

and

$$n_i \left[-\frac{k^2 dU_0 J_0}{\phi \kappa} I_4 + \frac{U_0 d^2(DT_0 + g/C_p)}{\phi \kappa} I_2 \left\{ 1 - \frac{S}{|n|^2} \right\} \right] = 0 \quad \dots(19)$$

Now, multiplying equation (18) by n , and equating real and imaginary parts we get

$$\begin{aligned}
 J_0 k I_3 n_r - \frac{k^2 dU_0 J_0}{\phi \kappa} (n_r^2 + n_i^2) I_4 + \frac{U_0 d^2(DT_0 + g/C_p)}{\phi \kappa} \left[k^{-1} R_e^{-1} n_r I_1 \right. \\
 \left. + \{k^{-1} R_D^{-1} n_r - n_r^2 + n_i^2\} I_2 - S I_2 \right] = 0 \quad \dots(20)
 \end{aligned}$$

and $n_i \left[\frac{U_0 d^2(DT_0 + g/C_p)}{\phi \kappa} \{k^{-1} R_e^{-1} I_1 + (k^{-1} R_D^{-1} - 2n_r) I_2\} + J_0 k I_3 \right] = 0 \quad \dots(21)$

4. Results and Discussion

Now we have some results and theorems:

Result 1: Equation (19) is interesting in the sense that where as it does not allow oscillatory modes to exist in the absence of a magnetic field, there is a possibility of oscillatory modes to exist in the presence of magnetic field, this discussion holds for $DT_0 + g/C_p < 0$.

Result 2: It follows from equation (18) that unstable modes can exist only when $DT_0 + g/C_p$ is negative.

Theorem 1. For oscillatory modes whether stable or unstable under the condition $DT_0 + g/C_p < 0, n_r$ and n_i must lie inside the circle $|n|^2 = S$.

Proof: Proof follows from equation (19).

Theorem 2. The necessary condition for instability is that $DT_0 + g/C_p < 0$.

Proof: Proof follows from equation (18).

Theorem 3. If $DT_0 + g/C_p > 0$, then the modes are stable.

Proof: Equation (18) can be rewritten as

$$\begin{aligned} n_r & \left[\frac{k^2 d U_0 J_0}{\phi \kappa} I_4 + \frac{U_0 d^2 (DT_0 + g/C_p)}{\phi \kappa} I_2 + \frac{U_0 d^2 (DT_0 + g/C_p)}{\phi \kappa} \frac{S}{|n|^2} I_2 \right] \\ & = J_0 k I_3 + \frac{U_0 d^2 (DT_0 + g/C_p)}{\phi \kappa} k^{-1} R_e^{-1} I_1 + \frac{U_0 d^2 (DT_0 + g/C_p)}{\phi \kappa} k^{-1} R_D^{-1} I_2 \end{aligned}$$

Obviously $n_r > 0$ if $DT_0 + g/C_p > 0$.

Hence the modes are stable.

Theorem 4: If unstable modes are oscillatory then the necessary condition is

$$|n_r| < \frac{J_0 k \phi \kappa I_3}{U_0 d^2 |DT_0 + g/C_p|}.$$

Proof : Let the modes be unstable and oscillatory so that $n_r < 0$ and $n_i \neq 0$.

Then we must necessarily have, in view of equation (21).

$$n_i \left[-\frac{U_0 d^2}{\phi \kappa} |DT_0 + g/C_p| \left\{ k^{-1} R_e^{-1} I_1 + k^{-1} R_D^{-1} I_2 + 2|n_r| I_2 \right\} + J_0 k I_3 \right] = 0.$$

For oscillatory modes, the above equation becomes

$$\frac{U_0 d^2}{\phi \kappa} |DT_0 + g/C_p| k^{-1} (R_e^{-1} I_1 + k^{-1} R_D^{-1} I_2) + \frac{U_0 d^2}{\phi \kappa} |DT_0 + g/C_p| \cdot 2 |n_r| |I_2 - J_0 k I_3| = 0$$

For the validity of the above equation, we must necessarily have

$$\frac{U_0 d^2}{\phi \kappa} |DT_0 + g/C_p| \cdot 2 |n_r| |I_2 - J_0 k I_3| < 0$$

or $|n_r| < \frac{J_0 k \phi \kappa I_3}{U_0 d^2 |DT_0 + g/C_p|}$

which is the required condition.

Now multiplying by C on both sides of equation (12), also substituting $iC = n$, and then dividing both sides by n , we get

$$k^{-1} R_e^{-1} (D^2 - k^2)^2 w - (k^{-1} R_D^{-1} - n) (D^2 - k^2) w = -\frac{S}{n} (D^2 - k^2) w + J_0 k \theta \tag{22}$$

Also substituting $k_x = k$ and $iC = n$ in equation (13) also dividing both sides by κ , we get

$$\left(D^2 - k^2 + \frac{kdU_0 n}{\phi \kappa} \right) \theta = \frac{U_0 d^2 (DT_0 + g/C_p)}{\phi \kappa} w \tag{23}$$

Now we eliminate θ from equations (22) and (23).

Multiplying equation (23) by $J_0 k$ and substituting the value of $J_0 k \theta$ from equation (22) in equation (23) we get

$$\begin{aligned}
 & k^{-1}R_e^{-1}(D^2 - k^2)^3 w - (k^{-1}R_D^{-1} - n)(D^2 - k^2)^2 w + \frac{S}{n}(D^2 - k^2)^2 w \\
 & + \frac{kdU_0 n}{\phi\kappa} \left[k^{-1}R_e^{-1}(D^2 - k^2)^2 w - (k^{-1}R_D^{-1} - n)(D^2 - k^2)w + \frac{S}{n}(D^2 - k^2)w \right] \\
 & = \frac{U_0 d^2 (DT_0 + g/C_p)}{\phi\kappa} J_0 k w. \quad \dots(24)
 \end{aligned}$$

Now multiplying equation (24) by w^* (the complex conjugate of w) and integrating over the range of z , we get

$$\begin{aligned}
 & -k^{-1}R_e^{-1}I_1 + \left(n - k^{-1}R_D^{-1} + \frac{S}{n} + \frac{dU_0 n R_e^{-1}}{\phi\kappa} \right) I_2 \\
 & + \frac{kdU_0 n}{\phi\kappa} \left(-n + k^{-1}R_D^{-1} - \frac{S}{n} \right) I_3 = \frac{U_0 d^2 (DT_0 + g/C_p)}{\phi\kappa} J_0 k I_4 \quad \dots(25)
 \end{aligned}$$

where $I_1 = \int \left(|D^2 w|^2 + 3k^2 |D^2 w|^2 + 3k^4 |Dw|^2 + k^6 |w|^2 \right) dz,$

$$I_2 = \int \left(|D^2 w|^2 + 2k^2 |Dw|^2 + k^4 |w|^2 \right) dz,$$

$$I_3 = \int \left(|Dw|^2 + k^2 |w|^2 \right) dz$$

and $I_4 = \int |w|^2 dz.$

On simplification, equation (25) reduces to

$$an^3 + 3bn^2 + 3cn + d = 0, \quad \dots(26)$$

where $a = \frac{kdU_0}{\phi\kappa} I_3,$

$$b = -\frac{1}{3} \left(I_2 + \frac{dU_0 R_e^{-1}}{\phi\kappa} I_2 + \frac{dU_0 R_D^{-1}}{\phi\kappa} I_3 \right),$$

$$c = \frac{1}{3} \left(k^{-1} R_e^{-1} I_1 + k^{-1} R_D^{-1} I_2 + \frac{k d U_0}{\phi \kappa} S I_3 + \frac{U_0 d^2 (D T_0 + g / C_p)}{\phi \kappa} J_0 k I_4 \right)$$

and $d = -S I_2,$

Now, if n_1, n_2, n_3 are the roots of the equation (26), then

$$n_1 + n_2 + n_3 > 0. \tag{27}$$

$$n_1 n_2 n_3 > 0 \tag{28}$$

and $n_1 n_2 + n_2 n_3 + n_3 n_1 = \frac{3C}{a} . \tag{29}$

Now, we shall prove some important theorems:

Theorem 5 : *The system is unstable under the condition $C < 0$.*

Proof: It follows from equation (29) that if $C < 0$, then its R.H.S. is negative. For L.H.S. to be negative, one or two roots should be negative necessarily, if all roots are real of equation (29) and inequality (28), if this equation has a pair of complex roots, then either the complex roots have negative real parts or otherwise the third root should be negative.

Theorem 6 : *Two disturbances grow and one decays under the condition $C < 0$.*

Proof : Proof follows from inequality (28) and equation (29).

A Particular case : In the absence of magnetic field we must necessarily have, $d = 0$. Thus equation (26) reduces to $n(an^2 + 3bn + 3c) = 0$, assuming that $n \neq 0$, then we have $an^2 + 3bn + 3c = 0$.

If n_1, n_2 are the roots of the above equation, then we have

$$n_1 + n_2 = -\frac{3b}{a} \tag{30}$$

$$\text{and } n_1 n_2 = \frac{3c}{a}. \quad \dots(31)$$

Theorem 7 : *The system is stable under the condition $c < 0$.*

Proof: Proof follows from equation (31) i.e. if $c < 0$, then one root is positive and one is negative. Hence the system is stable.

Theorem 8 : *For $c > 0$, the system is unstable under the condition $3b^2 > 4ac$.*

Proof: Proof is obvious.

Using the suitable transformation, equation (26) can be rewritten as

$$Z^3 + 3HZ + G = 0, \quad \dots(32)$$

$$\text{where } Z = an + b = \frac{kdU_0}{\phi\kappa} . n - \frac{1}{3} \left(I_2 + \frac{dU_0 R_e^{-1}}{\phi\kappa} I_2 + \frac{dU_0 R_D^{-1}}{\phi\kappa} I_3 \right),$$

$$\begin{aligned} G = a^2 d - 3abc + 2b^3 = & - \left(\frac{kdU_0}{\phi\kappa} \right)^2 . SI_2 \\ & + \frac{1}{3} \left(\frac{kdU_0}{\phi\kappa} \right) \left(I_2 + \frac{dU_0 R_e^{-1}}{\phi\kappa} I_2 + \frac{dU_0 R_D^{-1}}{\phi\kappa} I_3 \right) \\ & \left(k^{-1} R_e^{-1} I_1 + k^{-1} R_D^{-1} I_2 + \frac{kdU_0}{\phi\kappa} SI_3 - \frac{U_0 d^2 (DT_0 + g/C_p)}{\phi\kappa} J_0 k I_4 \right) \\ & - \frac{2}{27} \left(I_2 + \frac{dU_0 R_e^{-1}}{\phi\kappa} I_2 + \frac{dU_0 R_D^{-1}}{\phi\kappa} I_3 \right)^3 \end{aligned}$$

$$\begin{aligned} \text{and } H = ac - b^2 = & \frac{1}{3} \left(\frac{kdU_0}{\phi\kappa} \right) \left(k^{-1} R_e^{-1} I_1 + k^{-1} R_D^{-1} I_2 + \frac{kdU_0}{\phi\kappa} SI_3 \right. \\ & \left. - \frac{U_0 d^2 (DT_0 + g/C_p)}{\phi\kappa} J_0 k I_4 \right) - \frac{1}{9} \left(I_2 + \frac{dU_0 R_e^{-1}}{\phi\kappa} I_2 + \frac{dU_0 R_D^{-1}}{\phi\kappa} I_3 \right)^2. \end{aligned}$$

Theorem 9 : *The modes whether stable or unstable are non-oscillatory under the condition $G^2 + 4H^3 < 0$.*

Proof: If $G^2 + 4H^3 < 0$, then all the roots of the cubic equation (32) are real and different. Hence the modes whether stable or unstable are non-oscillatory under the condition $G^2 + 4H^3 < 0$.

Acknowledgement

I am thankful to *Prof. S.C. Agrawal* and *Dr. Ruchi Goel* for his expert guidance and kind cooperation in completion of this paper.

References

- [1]. Banerjee, M.B. and Agrawal, S.C. (1968). Thermal instability of parallel shear flows in the presence of adverse and non-adverse temperature gradients. *Jpn. J. Appl. Phys.*, **7**, 689-694.
- [2]. Bansal, N. and Agrawal, S.C. (1999). Thermal instability of a compressible shear flow in the presence of a weak applied magnetic field, *Proc. Nat. Acad. Sci. India*, **69** (A), III, 327-338
- [3]. Beck, J.L. (1972). Convection in a box of porous material saturated with fluid, *Phys. Fluids*, **15**, 1377-1383.
- [4]. Brinkman, H.C. (1947). A calculation of the viscous force exerted by a flowing fluid on a dense swarm of particles, *Appl. Sci. Res.*, **A1**, 27-34.
- [5]. Chand, S. and Agrawal, S.C. (1981). Thermal Instability of Shear Flows with a Compressibility Effect, *Jpn. J. Appl. Phys.*, **20**, 2237-2242.
- [6]. Darcy, H.P.C. (1856). *Les Fontains Publiques de la ville de Dijon*, Paris : Victor Dalmont.

- [7]. Gilman, P.A. (1970) . Instability of magnetohydrostatic stellar interiors from magnetic buoyancy, *The Astrophysical Journal* ,**162**, 1019-1029.
- [8]. Irmay, S. (1958). On the theoretical derivation of Darcy and Forchheimer formulaes, *Trans. Am. Geophys. Un.* **39**, 702-707.
- [9]. Jaimala and Agrawal, S.C. (1991). Shear flow instability in a porous medium, *Indian J. Pure Appl. Math.*, **22** (7), 611-625.
- [10]. Jain, M.K. (1981). *Stability of Stratified Shear Flows*, *Ph.D. Thesis*, Meerut University, Meerut.
- [11]. Jeffreys, H. (1930). The Theory of Hydrodynamic Stability, *Proc. Cambridge Phil. Soc.* **26**, 170-172.
- [12]. Kent, A. (1966) . Instability of laminar flow of a perfect magnetfluid, *Phys. Fluids*, **9**, 1286-1289.
- [13]. Scheidegger, A.E. (1960). Growth of instabilities on displacement fronts in porous media, *Phys. Fluid.*, **1**, 94-104.
- [14]. Spiegel, E.A. and Veronis, G. (1960) . On the Boussinesq approximation for a compressible fluid, *Astrophys. J.*, **131**, 442-447.
- [15]. Yih, C.S. (1961). Flow of a non-homogenous fluid in a porous medium, *J. Fluid Mech.*, **10**, 133-140.